## **HYDRAULIC PULLERS** PULLERS

REACH

¥

No. 1062 & 1063

No. 1070 & 1071

SPREAD

minus 4-7/8" when using leg ends.

Usable reach equals leg length

## Hydraulic Push-Puller®

No. 1062, 1063 - 17-1/2" Ton Capacity Can be used with Nos. 1124 and 1130 bearing pulling attachments or No. 680 pulley pulling attachment. May also be used with No. 1154 internal pulling attachment. Ends of legs are threaded 5/8"-18. Usable reach: 11-5/8"

Tool No.	Max. Reach	Max. Spread	Screw Size	Notes /	Weight			
1063	18-1/2"	5-3/4"-11-3/4"	1"-8 x 20"	hyd. ram		djusting	24827 leg end screw, and No	
1062	18-1/2"	5-3/4"-11-3/4"	1"-8 x 20"	Puller or	nly. 22 lbs.			
Extra Legs	(pair) for No. 1	L062, 1063 (Reacl	n equals leg leng	gth plus 2" w	ith leg end ca	ips.)		
Tool No.	Leg Length	ઈ Wt.		Tool No.	Leg Length	& Wt.		
1107	4-1/2" 2 lbs., 8 oz.			1105	22-1/2" 9 lbs.	-		
1106	9-1/2" 4 lbs., 8 oz.			1108	30" 11.5 lbs.	_	-	
1104	16-1/2" 6 lbs., 8 oz.			Note: 3/4 on leg up	F−14 thread	←	LEG LENGTH	<b>→</b>

No. 1070, 1071 - 30-Ton Capacity Can be used with Nos. 1126 and 1127 bearing pulling attachments or No. 680 pulley pulling attachment (two No. 8012 adapters are required to connect No. 680 to puller). Also may be used with No. 1166 internal pulling attachment. Ends of legs are threaded 1"-14. Usable reach: 12-1/8".

		1 5							
Usable reach equals leg length minus 5-7/8" when using leg ends.	Tool No.	Max. Reach	Max. Spread	Screw Size	3	Notes / Weight			
minus 5-778 when using leg ends.	1071	20-1/2"	7"-16-1/4"	1-1/4"-7	x 24"	Puller with No. 1110 legs, No. 28390 leg ends,	No. 4121		
No. 1076						nyd. ram, No. 34758 adjusting screw, and No.	27198		
Usable reach equals leg length						adjusting crank. 90 lbs.			
minus 10-5/8".	1070	20-1/2"	7"-16-1/4"	1-1/4"-7	x 24"	Puller only. 56 lbs.			
	Extra Legs (pair) for No. 1070, 1071 (Reach equals leg length plus 2-5/8" with leg end caps.)								
<b>No. 1076</b> – 50-Ton Capacity Can	Tool No	Leg Length &	Wt		Т	ool No. Leg Length & Wt.			
be used with Nos. 1128 and 1129	1109	8"				<b>111</b> 28"			
bearing pulling attachments. Ends	1109								
of legs are threaded 1-1/4"-12.		8 lbs.				22 lbs.			
Usable reach: 13-3/8". See page 135 to order threaded adapters for	1110 18"			N	Note: 1"-14 thread				
use with these pullers.		15 lbs. 🗖			С	n leg upper end.			
· · · · · · · · · · · · · · · · · · ·			-						
Tool No. Max. Reach Ma	ax. Spread	Screw S	ize		Notes / \	Veight			
<b>1076</b> 24" 8	8-1/2"- 20-	1/2" 1-5	5/8"– 5-1/2" x 30	)-3/8"	Puller or	ly. 106 lbs.			
Extra Legs (pair) for No. 1076 (Reach equals leg length plus 1-1/4"–12 thd. on both leg ends.)									
Tool No. Leg Length & Wt.				Tool No.	Leg Le	ngth & Wt.			
<b>1112</b> 24" 34 lbs.				1113	34" 47	bs.			

## Hydraulic Grip-O-Matic<sup>®</sup> Puller

No. 1060-1080 Available in 10 to 50-ton capacities. Reliable single-acting Power Twin ram is matched with a versatile 2-jaw or 3-jaw puller. Lightweight ram can be used in other applications. You also get an adjusting screw, speed crank, and coupler where applicable. Hydraulic pump is not included; see index for pump listings.

Tool No.	Reach	MAX Spread	Ram Capacity & Number	J Thickne Width	AW ess	Screw Size& Crank No.	Style and Weight		لل ا	Π.
1060	10"	17"	N/A	9/16"	1"	N/A	10-Ton, 2/3-Jaw;Puller Only; 17 lbs.	ATTEN	. 731	
1065	11-1/2"	16"	17-1/2 Ton, No. 4120	13/16"	1-9/32"	1"-8 x 20" No. 24814	17-1/2 Ton, 2-Jaw;40 lbs.			
1064	11-1/2"	16"	N/A	13/16"	1-9/32"	N/A	17-1/2 Ton, 2-Jaw Puller Only; 24 lbs.		'	1
1067	11-1/2"	20"	17-1/2 Ton, No. 4120	13/16"	1-9/32"	1"-8 x 20" No. 24814	17-1/2 Ton, 3-Jaw;53 lbs.	1060	10	75
1066	11-1/2"	20"	N/A	13/16"	1-9/32"	N/A	17-1/2 Ton, 3-Jaw Puller Only; 37 lbs.	Puller componen		Consciller
1073	19-7/16	5" 26"	30-Ton, No. 4121	1-1/8"	1-5/8"	1-1/4"-7 x 24" No. 27198	30-Ton, 2-Jaw;91 lbs.		Description Speed Crank Speed Crank	Capacity 17-1/2 Ton 30 Ton
1072	19-7/16	5" 26"	N/A	1-1/8"	1-5/8"	N/A	30-Ton, 2-JawPuller Only; 59 lbs.	29595	Speed Crank	50 Ton
1075	19-7/16	5" 34"	30-Ton, No. 4121	1-1/8"	1-5/8"	1-1/4"-7 x 24" No. 27198	30-Ton, 3-Jaw;122 lbs.		Adjusting Screw	
1074	19-7/16	5" 34"	N/A	1-1/8"	1-5/8"	N/A	30-Ton, 3-Jaw Puller Only; 90 lbs.		Adjusting Screw Lube for pullers	50 Ion
1080	19-7/16	5" 44"	N/A	1-1/8"	1-5/8"	N/A	50-Ton, 3-Jaw Puller Only; 187 lbs.			

otctools.com